



STORAGE CAPACITY	3000	L
APPROX. WEIGHT WHEN EMPTY	400	kg
MAXIMUM POWER INPUT	132	kW
MAXIMUM STORED WATER TEMPERATURE	85	°C
T&PR VALVE SETTING	700	kPa
EXPANSION CONTROL VALVE (ECV) SETTING	550	kPa
MAXIMUM WATER SUPPLY PRESSURE:		
WITHOUT ECV FITTED	560	kPa
WITH ECV FITTED	450	kPa

PARTS SUPPLIED WITH STORAGE TANK:

1. AQ0901156 - INSTRUCTIONS RHEEM RW 2205 COMMERCIAL (QTY:1)
2. AQ0262015 - VALVE PTR25-700 700kPa (QTY:1)
3. BR738 GASKET RHEEM ELEMENT 300NB x 3mm EDPM (QTY:1)
4. FA212 SCREW M12 x 30 SS 304 (QTY:16)
5. FA213 WASHER SPRING M12 SS 304 (QTY:16)
6. ANTI SEIZE GREASE (QTY:1)

PACKAGING:

- CELLAIRE FOAM
- PALLET COVER (CLEAR)
- STRETCH WRAP (CLEAR)
- CRATE RW3050 OPEN SLAT/PALLET BASE
- EXTERNAL DIMENSIONS (WxDxH): 1535mm x 1535mm x 3295mm

NOTES:

1. TANK AND FITTING MATERIAL: 2205 STAINLESS STEEL
2. OUTER CASE MATERIAL: WHITE PAINTED STEEL WITH WHITE GALVANISED POWDERCOATED ENDS
3. FITTING SHROUD MATERIAL: PAINTED STAINLESS STEEL PLATES WITH STAINLESS STEEL SCREWS
4. SHIELDING OF WELDS: INERT BACKING GAS
5. PICKLING: WELDS HAND PICKLED
6. INSULATION: POLYURETHANE FOAM
7. WATERMARK LICENCE: WM-000353
8. EXPANSION CONTROL VALVE (ECV) NOT SUPPLIED WITH TANK
9. TOLERANCES:  
VERTICAL DIMENSIONS: ±20mm  
HORIZONTAL DIMENSIONS: ±10mm
10. NOT ALL TANK LABELS SHOWN ON THIS DRAWING. FOR REMAINING LABELS REFER DRAWING AQ0907090



AM230205	A	DRAWING RELEASED	08/11/23	MT	AP	TW
EPCR	REV	DESCRIPTION	DATE	DSGR	CHKD	APPR
<b>RHEEM AUSTRALIA PTY LTD</b>			PART		SHT	
This drawing and the information it contains is the exclusive property of: RHEEM AUSTRALIA Pty Ltd. It must not be reproduced, in whole or in part, without written permission from: RHEEM AUSTRALIA Pty Ltd.			AQ9643002		1/1 A3	
TOLERANCES UNLESS NOTED OTHERWISE No (0) Decimals ..... +/- 1.0 mm One (1) Decimal ..... +/- 0.5 mm Two (2) Decimals ..... +/- 0.25 mm Angles ..... +/- 1 Degree			DESCRIPTION		3000L RW3050N7U UP FL SS	
THIRD ANGLE PROJECTION			DRAWN		DATE	
ALL DIMENSIONS IN MILLIMETRES			MT		26/09/2023	
DO NOT SCALE			PASSED		TW	