



RHEEM EZ LINK® - LINKED CONTINUOUS FLOW HOT WATER SYSTEM



GAS



5 STAR RATING

1-6

PERSONS

3-54
L/MIN

CAPACITY

10
YEAR

DOMESTIC WARRANTY³



FOR COMMERCIAL & DOMESTIC APPLICATIONS

Links two Rheem Continuous Flow gas water heaters for up to 54L/minute capacity



INSTALL A RHEEM®





RHEEM EZ LINK® - LINKED CONTINUOUS FLOW HOT WATER SYSTEM

NEW Rheem EZ Link® seamlessly links two Rheem Continuous Flow gas water heaters to deliver up to **54L/Minute**¹ of continuous flow hot water, without ever running out.

Rheem EZ Link® performance features:

- Suitable for use with all Rheem 18, 20 and 27 Litres/Minute Continuous Flow gas water heaters, which are EZ Link® ready
- Flexible delivery of any volume between 3 and 54 Litres/Minute¹
- Staged heating, so energy usage corresponds only to the hot water demand
- 2 units means no loss of hot water in the event of a unit breakdown
- Longer unit life, as each unit carries a lighter load
- Remote Controller display for easy fault diagnosis and service
- Simple control via a Rheem Remote Temperature Controller, offering flexible temperature settings (up to 60°C²) and full electronic temperature control for extra protection against scalding



The Rheem EZ Link® kit contains all you need to install this system:

- EZ Link® cable
- Cable clamps and mounting screws

SPECIFICATIONS	Model Number	Part Number
EZ Link® System Kit (1.8 M cable and fittings)	–	290141
Rheem 18 Continuous Flow:		
50 Degrees	876018	–
60 Degrees	874018	–
Rheem 20 Continuous Flow:		
50 Degrees	876020	–
60 Degrees	874020	–
Rheem 27 Continuous Flow:		
50 Degrees	876027	–
60 Degrees	874027	–
Temperature Controller:		
Kitchen	–	299850
Bathroom	–	299851
Deluxe Temperature Controller:		
Kitchen	–	299858
Bathroom	–	299859

¹ Guide only, subject to ambient water temperature and pressure, correct pipe sizing and appliance flow rates.

² 50°C factory preset models supply hot water at a maximum 50°C at all outlets in accordance with AS3498. Some applications may require tempering, refer to AS3500.4. 60°C and higher models must have a tempering valve installed in accordance with AS3500.4.

³ Warranty: 10 years parts & labour on heat exchanger, 3 year parts & labour warranty on all other components, for Domestic (Non-commercial) installations only. Commercial Warranty: 5 years parts & labour on heat exchanger, 1 year warranty on all other components.

Rheem Australia Pty Ltd. Head Office

1 Alan Street, Rydalmere, New South Wales 2116, Australia
PO Box 6, Rydalmere, New South Wales 2116, Australia

*Registered Trademark of Rheem Australia Pty Ltd.

